



BC 4X4



2,000 to 6,000 # Capacity

4-WHEEL DRIVE BURDEN CARRIER



Photo may show optional equipment

***Trowin Industries, Inc.***

3925 N Hastings Way \* Eau Claire, WI 54703

715-839-7966 PH \* 715-833-2181 FX

[www.trowin.com](http://www.trowin.com)

specifications



# BC 4x4

2,000 to 6,000 Capacity  
4-Wheel Drive Heavy Duty  
Industrial Burden Carrier



**Engine:** Ford 2.5 ltr 4-Cylinder EFI Gasoline Engine w/ Engine Shut-Down System (*std*)

**Transmission:** PR-1 Automatic Transmission w/ Torque Converter, 1 Speed Forward & Reverse

**Drop Box:** Full Time, Heavy Duty Industrial Type

**PTO:** Transmission Mount, Internal Chain Drive with SAE 'A' or 'B' Flange

**Drive Axle:** Heavy Duty Automotive Type Mounted on Leaf Springs

**Drive Steer Axle:** Heavy Duty Automotive Type w/ lock-Out Hubs Mounted on Leaf Springs

**Brakes:** Service; 4-Wheel Split System, Power Assisted Disc Brakes Parking; Lever Operated on Drop Box Output

**Steering:** Full-Time Power Assisted, Hydrostatic System

**Electrical System:** 12-Volt Negative Ground, 85 Amp Alternator, Keyed Anti-Restart Ignition, Horn, Sealed Beam Headlights (2), Sealed Beam Stop/Tail Lights (2)

**Instrumentation:** Gauges: Engine Hour Meter, Water Temperature, Fuel Level Warning Lights: Engine Temperature, Low Oil Pressure, Transmission Temperature, Voltage, Brake System Failure, Parking Brake Engaged

**Tires:** 24-12x12 6 ply Pneumatic Foam Fill, Solid, Soft Ride Solid (*optional*)

**Seat:** Single Operator Metal Pan w/ Vinyl Padding & Adjuster

**Frame:** Laser Cut, Unitized All Welded Heavy Duty Construction, 8x3 Tubing Frame Rails, 3/8" Body Components, 1" Main Frame, Media Blasted for Superior Finish Adhesion

**Finish:** Primer: 2-part Grey Epoxy Primer Finish: 2-part Polyurethane (White, Yellow or Orange)(*std*)

**Options:** LPG, CNG, Diesel, Electric, Overhead Guard, Cab, Heater/Defroster, Back-up Alarm, Turn Signals, Tilt Steering, Suspension Seat, Couplers, Other Options Available Please Consult Dealer or Factory

<b>Model #</b>	BC4-20	BC4-30	BC4-40	BC4-50	BC4-60
<b>Capacity(lbs)</b>	2,000	3,000	4,000	5,000	6,000

