



BC-L



14,000 to 24,000 lb Capacity

## INDUSTRIAL BURDEN CARRIER



# *TROWIN INDUSTRIES, INC.*

PO Box 1778 \* Eau Claire, WI 54702  
715-839-7966 PH \* 715-833-2181 FX  
[www.trowin.com](http://www.trowin.com) \* [info@trowin.com](mailto:info@trowin.com)

specifications



# BC-L

## 14,000 to 24,000 lbs Capacity Industrial Burden Carrier



**Engine:** Cummins B4.5 ltr. 4-cylinder Diesel Engine, 80 hp(Tier 3 Compliant)  
Zenith 4.4 ltr. 6-cylinder EFI Gasoline Engine w/ shutdown system (Tier 3 Compliant)

**Transmission:** Ford (Certified) C-6 Automatic Transmission, 2 or 3 Speeds Forward & 1 Reverse (w/ Cummins or I-6 ns)

**Drive Axle:** Heavy Duty Automotive Type, Leaf Spring Mounted

**Steer Axle:** Heavy Duty Industrial Beam, Leaf Spring Mounted

**Brakes:** Service; 4-Wheel Split System, Power Assisted Disc Brakes Parking; Lever Operated on Transmission Output

**Steering:** Full-Time Power Assisted, Hydrostatic System

**Electrical System:** 12-Volt Negative Ground, 95 Amp Alternator, Keyed Anti-Restart Ignition, Horn, Sealed Beam Headlights (2), Sealed Beam Stop/Tail Lights (2)

**Instrumentation:** Gauges: Engine Hour Meter, Water Temperature, Fuel Level Warning Lights: Engine Temperature, Low Oil Pressure, Transmission Temperature, Voltage, Brake System Failure, Parking Brake Engaged

**Tires:** 265/70R19 Pneumatic, Single Front: 255/70R22.5 Dual Rear

**Seat:** Single Operator Polyurethane Foam Seat; For & Aft Adjuster

**Frame:** Laser Cut, Unitized All Welded Heavy Duty Construction, 8x3 Tubing Frame Rails, 3/8" Body Components, Media Blasted for Superior Finish Adhesion

**Finish:** Primer: 2-part Grey Epoxy Primer Finish: 2-part Polyurethane (White, Yellow or Orange)(std)

**Options:** LPG, CNG, Diesel, Electric, Overhead Guard, Cab, Heater/Defroster, Back-up Alarm, Turn Signals, Tilt Steering, Suspension Seat, Couplers, Other Options Available Please Consult Dealer or Factory

| Model #       | BCL-140 | BCL-160 | BCL-180 | BCL-200 | BCL-220 | BCL-240 |
|---------------|---------|---------|---------|---------|---------|---------|
| Capacity(lbs) | 14,000  | 16,000  | 18,000  | 20,000  | 22,000  | 24,000  |



specifications subject to change without notice

Last Update 1/1/08